

Package ‘PreProcessing’

January 20, 2025

Type Package

Title Various Preprocessing Transformations of Numeric Data Matrices

Date 2021-06-16

Version 0.1.0

Author Swamiji Pravedson

Maintainer Swamiji Pravedson <swamiji.pravedson@gmail.com>

Description Preprocess numeric data matrices into desired transformed representations. Standardization, Unitization, Cubitization and adaptive intervals are offered.

License GPL-3

Encoding UTF-8

RoxygenNote 7.1.1

Imports stats (>= 1.0.1), ggplot2 (>= 1.0.1)

Suggests knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2021-06-24 12:00:02 UTC

Contents

cubitize	2
intervalize	2
standardize	3
unitize	4

Index	6
--------------	----------

cubitize	<i>Cubitizes the matrix given as input</i>
----------	--

Description

Cubitizes the matrix given as input

Usage

```
cubitize(xx)
```

Arguments

xx Matrix or a data frame of numeric entries

Value

Matrix with columns that have minimum zero and maximum one

Examples

```
## Not run:
# I don't want you to run this

## End(Not run)
n<-450; x <- data.frame(cbind(rnorm(n, 162, 4), rnorm(n, 108, 2),
rnorm(n, 117, 3), rnorm(n, 36, 2), rnorm(n, 45, 2)))
p <- ncol(x)
x.cube <- cubitize(x)
round(head(x),2)
round(head(x.cube),2)
round(rbind(apply(x, 2, min), apply(x.cube, 2, min)),2)
round(rbind(apply(x, 2, max),apply(x.cube, 2, max)),2)
oldpar<-par(mfrow=c(1,2))
boxplot(x[,1:min(5,p)], main='Original Data', col=rainbow(9))
boxplot(x.cube[,1:min(5,p)], main='PreProcessed Data', col=rainbow(7))
par(oldpar)
```

intervalize	<i>Intervalizes the matrix given as input</i>
-------------	---

Description

Intervalizes the matrix given as input

Usage

```
intervalize(xx, a = -1, b = 1)
```

Arguments

xx Matrix or a data frame of numeric entries
a lower bound of the target interval
b upper bound of the target interval

Value

Matrix with columns that have minimum zero and maximum one

Examples

```
## Not run:
# I don't want you to run this

## End(Not run)
n<-450; x <- data.frame(cbind(rnorm(n, 162, 4), rnorm(n, 108, 2),
rnorm(n, 117, 3), rnorm(n, 36, 2), rnorm(n, 45, 2)))
p <- ncol(x)
x.inter <- intervalize(x,a=-1,b=1)
round(head(x),2)
round(head(x.inter),2)
round(rbind(apply(x, 2, min), apply(x.inter, 2, min)),2)
round(rbind(apply(x, 2, max),apply(x.inter, 2, max)),2)
oldpar<-par(mfrow=c(1,2))
boxplot(x[,1:min(5,p)], main='Original Data', col=rainbow(9))
boxplot(x.inter[,1:min(5,p)], main='PreProcessed Data', col=rainbow(7))
par(oldpar)
```

standardize

Standardizes the matrix given as input

Description

This function takes as input a matrix of numeric values and then transforms it so that each column has a mean of zero and a variance of one

Usage

```
standardize(xx)
```

Arguments

xx Matrix or a data frame of numeric entries

Value

Matrix with columns that have mean zero and variance one

Examples

```
## Not run:
# I don't want you to run this

## End(Not run)
n<-450; x <- data.frame(cbind(rnorm(n, 162, 4), rnorm(n, 108, 2),
rnorm(n, 117, 3), rnorm(n, 36, 2), rnorm(n, 45, 2)))
p <- ncol(x)
x.stan <- standardize(x)
round(head(x),2)
round(head(x.stan),2)
round(rbind(apply(x, 2, mean), apply(x.stan, 2, mean)),2)
round(rbind(apply(x, 2, sd),apply(x.stan, 2, sd)),2)

oldpar <- par(mfrow=c(1,2))
boxplot(x[,1:min(5,p)], main='Original Data', col=rainbow(9))
boxplot(x.stan[,1:min(5,p)], main='PreProcessed Data', col=rainbow(7))
par(oldpar)
```

unitize

Unitizes the matrix given as input

Description

Unitizes the matrix given as input

Usage

```
unitize(xx)
```

Arguments

xx Matrix or a data frame of numeric entries

Value

Matrix with columns that have mean zero and length one

Examples

```
## Not run:
# I don't want you to run this

## End(Not run)
n<-450; x <- data.frame(cbind(rnorm(n, 162, 4), rnorm(n, 108, 2),
rnorm(n, 117, 3), rnorm(n, 36, 2), rnorm(n, 45, 2)))
p <- ncol(x)
x.unit <- unitize(x)
round(head(x),2)
```

```
round(head(x.unit),2)
round(rbind(apply(x, 2, mean), apply(x.unit, 2, mean)),2)
round(rbind(apply(x, 2, sd),apply(x.unit, 2, sd)),2)
oldpar<-par(mfrow=c(1,2))
boxplot(x[,1:min(5,p)], main='Original Data', col=rainbow(9))
boxplot(x.unit[,1:min(5,p)], main='PreProcessed Data', col=rainbow(7))
par(oldpar)
```

Index

cubitize, 2

intervalize, 2

standardize, 3

unitize, 4