

Package ‘SeedCalc’

October 12, 2022

Type Package

Title Seed Germination and Seedling Growth Indexes

Version 1.0.0

Author Laercio Junio da Silva, Andre Danta de Medeiros e Ariadne Morbeck Santos Oliveira

Maintainer Laercio Junio da Silva <laerciojdsilva@gmail.com>

Description Functions to calculate seed germination and seedling emergence and growth indexes. The main indexes for germination and seedling emergence, considering the time for seed germinate are: T10, T50 and T90, in Farooq et al. (2005) <10.1111/j.1744-7909.2005.00031.x>; and MGT, in Labouriau (1983). Considering the germination speed are: Germination Speed Index, in Maguire (1962), Mean Germination Rate, in Labouriau (1983); considering the homogeneity of germination are: Coefficient of Variation of the Germination Time, in Carvalho et al. (2005) <10.1590/S0100-84042005000300018>, and Variance of Germination, in Labouriau (1983); Uncertainty, in Labouriau and Valadares (1976) <ISSN:0001-3765>; and Synchrony, in Primack (1980). The main seedling indexes are Growth, in Sako (2001), Uniformity, in Sako (2001) and Castan et al. (2018) <doi:10.1590/1678-992x-2016-0401>; and Vigour, in Medeiros and Pereira (2018) <doi:10.1590/1983-40632018v4852340>.

License GPL (>= 2)

Encoding UTF-8

LazyData true

NeedsCompilation no

Repository CRAN

Date/Publication 2018-12-01 00:00:16 UTC

R topics documented:

SeedCalc-package	2
CVG	3
CVt	4
FGP	4
GermCalc	5
growth	6

GSI	7
mean_pa	7
mean_raiz	8
mean_razao	9
mean_total	9
MGR	10
MGT	11
PlantCalc	11
Sinc	13
T10	13
T50	14
T90	15
Unc	15
UnifG	16
unif_1	17
unif_2	17
VarGer	18
vigor	19
vigor_corr	20

Index	21
--------------	-----------

SeedCalc-package

Seed germination and seedling growth indexes

Description

Functions to calculate seed germination and seedling emergence and growth indexes.

The main indexes for germination and seedling emergence, considering the time for seed germinate are: T10, T50 (Farooq et al., 2005), T90 e MGT (Labouriau, 1983); considering the germination speed are: Germination Speed Index (Maguire, 1962), Mean Germination Rate (Labouriau, 1983); considering the homogeneity of germination are: Coefficient of Variation of the Germination Time (Carvalho et al., 2005) and Variance of Germination (Labouriau, 1983); Uncertainty (Labouriau & Valadares, 1976) and Synchrony (Primack, 1980).

The main seedling indexes are Growth, Uniformity and Vigour (Sako, 2001; Medeiros & Pereira, 2018).

Details

Package: SeedCalc
 Type: Package
 Version: 1.0.0
 Date: 2018-10-31
 License: GPL (>= 2)

Author(s)

Laercio Junio da Silva <laerciojdsilva@gmail.com.br>

Andre Dantas de Medeiros <medeiros.seeds@gmail.com >

Ariadne Morbeck Santos Oliveira <ariadneoliveira86@gmail.com>

Maintainer: Laercio Junio da Silva <laerciojdsilva@gmail.com>

References

CARVALHO, M. P., SANTANA, D. G., RANAL, M. A. (2005) <doi:10.1590/S0100-84042005000300018>

FAROOQ, M., BASRA, S. M. A., AHMAD, N., HAFEEZ, K. (2005) <doi:10.1111/j.1744-7909.2005.00031.x>

LABOURIAU L. G., VALADARES, M.B. (1976, ISSN:0001-3765)

LABOURIAU, L. G. (1983) Uma nova linha de pesquisa na fisiologia da germinação das sementes. Anais do XXXIV Congresso Nacional de Botânica. SBB, Porto Alegre, 11–50.

MAGUIRE, J. D. (1962) <doi:10.2135/cropsci1962.0011183X000200020033x>

MEDEIROS, A. D. DE, PEREIRA, M. D. (2018) <doi:10.1590/1983-40632018v4852340>

PRIMACK, R.B. (1980) <doi:10.2307/2259460>

SAKO, Y., MCDONALD, M. B., FUJIMURA, K., EVANS, A. F., BENNETT, M. A. A system for automated seed vigour assessment. Seed Science and Technology, v. 29, n. 3, p. 625–636, 2001.

CVG

Velocity of Germination Coefficient

Description

Calculates the Velocity of Germination Coefficient (Nichols & Heydecker, 1968).

Usage

CVG(time, nger)

Arguments

time	A vector object containing the time for germination.
nger	A vector object containing the accumulated number of seeds germinated at each time.

References

NICHOLS, M. A.; HEYDECKER, W. Two approaches to the study of germination data. Proceedings of the International Seed Testing Association, v. 33, p. 531–540, 1968.

Examples

```
time <- c(1,2,3,4,5,6,7,8,9,10)
nger <- c(0,2,4,15,25,38,45,50,50,50)
CVG(time,nger)
```

CVt*Germination Time Coefficient of variation*

Description

Calculates the Germination Time Coefficient of variation (Carvalho et al., 2005).

Usage

```
CVt(time,nger)
```

Arguments

time	A vector object containing the time for germination.
nger	A vector object containing the accumulated number of seeds germinated at each time.

References

CARVALHO, M. P.; SANTANA, D. G.; RANAL, M. A. Emergência de plântulas de *Anacardium humile* A. St.-Hil. (Anacardiaceae) avaliada por meio de amostras pequenas. *Revista Brasileira de Botânica*, v. 28, n. 3, p. 627–633, 2005.

Examples

```
time <- c(1,2,3,4,5,6,7,8,9,10)
nger <- c(0,2,4,15,25,38,45,50,50,50)
CVt(time,nger)
```

FGP*Final Percentage of Germination*

Description

Calculated the Final Percentage of Germination.

Usage

```
FGP(nger, Nseeds)
```

Arguments

nger It is a Vector object containing the accumulated number of seeds germinated.
Nseeds The total amount of seeds used for the germination or emergence test.

Examples

```
nger <- c(0, 2, 4, 15, 25, 38, 45, 50, 50, 50)  
FGP(nger, 50)
```

GermCalc

GermCalc Function

Description

Calculates all indices for seed germination or seedling emergence.

Usage

```
GermCalc(germdata, NSeeds)
```

Arguments

germdata A data.frame object. The first column is the time for germination, and the others are the total number of seeds germinated until each time
NSeeds The total amount of seeds used for the germination or emergence test.

Author(s)

Laercio Junio da Silva <laerciojdsilva@gmail.com.br> Andre Dantas de Medeiros <medeiros.seeds@gmail.com>
> Ariadne Morbeck Santos Oliveira <ariadneoliveira86@gmail.com>

Examples

```
time <- c(1, 2, 3, 4, 5, 6, 7, 8, 9, 10)  
rep1 <- c(0, 2, 4, 15, 25, 38, 45, 50, 50, 50)  
rep2 <- c(0, 4, 6, 18, 22, 39, 40, 48, 50, 50)  
germdata <- data.frame(time, rep1, rep2)  
GermCalc(germdata, 50)
```

growth *Seedling Growth Index*

Description

It calculates the Seedling Growth Index (Sako, 2001).

Usage

```
growth(lengths, wr = 90, wh = 10)
```

Arguments

lengths	A data.frame object containing seedling lengths data with four columns. The first and second columns are for identification, e.g. treatments and repetitions. The third is the shoot length and the fourth is the root length.
wr	A numeric value between zero and 100. Default is 90. Is the weight given to the root length in the Growth index calculation.
wh	A numeric value between zero and 100. Default is 10. Is the weight given to the shoot length in the Growth index calculation.

References

SAKO, Y.; MCDONALD, M. B.; FUJIMURA, K.; EVANS, A. F.; BENNETT, M. A. A system for automated seed vigour assessment. *Seed Science and Technology*, v. 29, n. 3, p. 625-636, 2001.

Examples

```
Seedling <- data.frame(
  LOTE = c(1, 1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 2),
  REP = c(1, 1, 1, 1, 2, 2, 2, 1, 1, 1, 1, 2, 2, 2, 2),
  SH = c(0.00, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 0.64, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 1.98),
  ROOT = c(4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 8.75)
)
print(Seedling)
Unif <- growth(Seedling, wr = 90, wh = 10)
Unif
```

GSI *Germination Speed Index*

Description

Calculates the Germination Speed Index (Maguire, 1982).

Usage

```
GSI(time, nger)
```

Arguments

time	A vector object containing the time for germination.
nger	A vector object containing the accumulated number of seeds germinated at each time.

References

MAGUIRE, J. D. Speed of germination-aid selection and evaluation for seedling emergence and vigor. *Crop Science*, v. 2, p. 176–177, 1962.

Examples

```
time <- c(1,2,3,4,5,6,7,8,9,10)
nger <- c(0,2,4,15,25,38,45,50,50,50)
GSI(time, nger)
```

mean_pa *Shoot Length*

Description

It calculates the Mean Shoot Length

Usage

```
mean_pa(lengths)
```

Arguments

lengths	A data.frame object containing seedling lengths data with four columns. The first and second columns are for identification, e.g. treatments and repetitions. The third is the shoot length and the fourth is the root length.
---------	--

Examples

```
Seedling <- data.frame(
  LOTE = c(1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 2),
  REP = c(1, 1, 1, 1, 2, 2, 2, 1, 1, 1, 1, 2, 2, 2, 2),
  SH = c(0.00, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 0.64, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 1.98),
  ROOT = c(4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 8.75)
)
print(Seedling)
SL <- mean_pa(Seedling)
SL
```

mean_raiz	<i>Root Length</i>
-----------	--------------------

Description

It calculates the Mean Root Length

Usage

```
mean_raiz(lengths)
```

Arguments

lengths A data.frame object containing seedling lengths data with four columns. The first and second columns are for identification, e.g. treatments and repetitions. The third is the shoot length and the fourth is the root length.

Examples

```
Seedling <- data.frame(
  LOTE = c(1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 2),
  REP = c(1, 1, 1, 1, 2, 2, 2, 1, 1, 1, 1, 2, 2, 2, 2),
  SH = c(0.00, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 0.64, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 1.98),
  ROOT = c(4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 8.75)
)
print(Seedling)
RL <- mean_raiz(Seedling)
RL
```

mean_razao	<i>Ratio Root-Shoot Length</i>
------------	--------------------------------

Description

It calculates the Mean Ration Root-Shoot Length

Usage

```
mean_razao(lengths)
```

Arguments

lengths	A data.frame object containing seedling lengths data with four columns. The first and second columns are for identification, e.g. treatments and repetitions. The third is the shoot length and the fourth is the root length.
---------	--

Examples

```
Seedling <- data.frame(
  LOTE = c(1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2),
  REP = c(1, 1, 1, 1, 2, 2, 2, 1, 1, 1, 1, 2, 2, 2),
  SH = c(0.00, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 0.64, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 1.98),
  ROOT = c(4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 8.75)
)
print(Seedling)
RSL <- mean_razao(Seedling)
RSL
```

mean_total	<i>Seedling Length</i>
------------	------------------------

Description

It calculates the Mean Seedling Length

Usage

```
mean_total(lengths)
```

Arguments

lengths	A data.frame object containing seedling lengths data with four columns. The first and second columns are for identification, e.g. treatments and repetitions. The third is the shoot length and the fourth is the root length.
---------	--

Examples

```
Seedling <- data.frame(
  LOTE = c(1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2),
  REP = c(1, 1, 1, 1, 2, 2, 2, 1, 1, 1, 1, 2, 2, 2),
  SH = c(0.00, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 0.64, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 1.98),
  ROOT = c(4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 8.75)
)

print(Seedling)
SLen <- mean_total(Seedling)
SLen
```

MGR

Mean Germination Rate

Description

Calculates the Mean Germination Rate (Labouriau, 1983). It is 1/MGT.

Usage

```
MGR(time, nger)
```

Arguments

time	A vector object containing the time for germination.
nger	A vector object containing the accumulated number of seeds germinated at each time.

References

LABOURIAU, L. G. (1983). Uma nova linha de pesquisa na fisiologia da germina??o das sementes. Anais do XXXIV Congresso Nacional de Botanica. SBB, Porto Alegre, 11-50.

Examples

```
time <- c(1,2,3,4,5,6,7,8,9,10)
nger <- c(0,2,4,15,25,38,45,50,50,50)
MGR(time, nger)
```

MGT	<i>Mean Germination Time</i>
-----	------------------------------

Description

Calculates the Mean Germination Time (Labouriau, 1983).

Usage

```
MGT(time, nger)
```

Arguments

time	A vector object containing the time for germination.
nger	A vector object containing the accumulated number of seeds germinated at each time.

References

LABOURIAU, L. G. (1983). Uma nova linha de pesquisa na fisiologia da germinação das sementes. Anais do XXXIV Congresso Nacional de Botânica. SBB, Porto Alegre, 11-50.

Examples

```
time <- c(1,2,3,4,5,6,7,8,9,10)
nger <- c(0,2,4,15,25,38,45,50,50,50)
MGT(time, nger)
```

PlantCalc	<i>PlantCalc Function</i>
-----------	---------------------------

Description

Calculates all indices for seedlings.

Usage

```
PlantCalc(lengths, Ger=100, wr = 90, wh = 10, wg = 0.7, wu = 0.3, Unif = 1)
```

Arguments

lengths	A data.frame object containing seedling lengths data with four columns. The first and second columns are for identification, e.g. treatments and repetitions. The third is the shoot length and the fourth is the root length.
Ger	A data.frame object containing two columns. The first must contain the identification of the treatments identical to the first column of the seedling length data. These values is used for vigor_corr calculation. The default is the numeric value 100 and in this case the vigor_corr is equal to vigor index.
wr	A numeric value between zero and 100. Default is 90. Is the weight given to the root lenght in the Growth index calculation.
wh	A numeric value between zero and 100. Default is 10. Is the weight given to the shoot lenght in the Growth index calculation.
wg	A numeric value between zero and one. Default is 0.7. Is the weight given to the seedling lenght in the Vigor index calculation.
wu	A numeric value between zero and one. Default is 0.3. Is the weight given to the Unif_2 index calculation.
Unif	A numeric value, 1 or 2. If 1, the unif_1 index is used for Vigor index calculation. If 2, the Unif_2 index is used for Vigor index calculation.

Author(s)

Laercio Junio da Silva <laerciojdsilva@gmail.com.br> Andre Dantas de Medeiros <medeiros.seeds@gmail.com>
> Ariadne Morbeck Santos Oliveira <ariadneoliveira86@gmail.com>

Examples

```
Seedling <- data.frame(
  LOTE = c(1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2),
  REP = c(1, 1, 1, 1, 2, 2, 2, 1, 1, 1, 1, 2, 2, 2),
  SH = c(0.00, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 0.64, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 1.98),
  ROOT = c(4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 8.75)
)
print(Seedling)
SeedlIndexes <- PlantCalc(Seedling)
SeedlIndexes

Ger <- data.frame(LOTE = c(1,2), GER = (c(90,80)))
print(Ger)

SeedlIndexes <- PlantCalc(Seedling, Ger)
SeedlIndexes
```


References

FAROOQ, M.; BASRA, S. M. A.; AHMAD, N.; HAFEEZ, K. Thermal Hardening: A New Seed Vigor Enhancement Tool in Rice. *Journal of Integrative Plant Biology*, v. 47, n. 2, p. 187-193, 2005.

Examples

```
time <- c(1,2,3,4,5,6,7,8,9,10)
nger <- c(0,2,4,15,25,38,45,50,50,50)
T10(time,nger)
```

T50

Time spent to 50 percent germination

Description

Calculates the time spent to 50 percent germination (Farooq et al., 2005).

Usage

```
T50(time,nger)
```

Arguments

time	A vector object containing the time for germination.
nger	A vector object containing the accumulated number of seeds germinated at each time.

References

FAROOQ, M.; BASRA, S. M. A.; AHMAD, N.; HAFEEZ, K. Thermal Hardening: A New Seed Vigor Enhancement Tool in Rice. *Journal of Integrative Plant Biology*, v. 47, n. 2, p. 187-193, 2005.

Examples

```
time <- c(1,2,3,4,5,6,7,8,9,10)
nger <- c(0,2,4,15,25,38,45,50,50,50)
T50(time,nger)
```

T90*Time spent to 90 percent germination*

Description

Calculates the time spent to 90 percent germination (Adapted from Farooq et al., 2005).

Usage

```
T90(time,nger)
```

Arguments

time	A vector object containing the time for germination.
nger	A vector object containing the accumulated number of seeds germinated at each time.

References

FAROOQ, M.; BASRA, S. M. A.; AHMAD, N.; HAFEEZ, K. Thermal Hardening: A New Seed Vigor Enhancement Tool in Rice. *Journal of Integrative Plant Biology*, v. 47, n. 2, p. 187-193, 2005.

Examples

```
time <- c(1,2,3,4,5,6,7,8,9,10)
nger <- c(0,2,4,15,25,38,45,50,50,50)
T90(time,nger)
```

Unc*Germination Uncertainty*

Description

Calculates the germination Uncertainty (Labouriau & Valadares, 1976).

Usage

```
Unc(time,nger)
```

Arguments

time	A vector object containing the time for germination.
nger	A vector object containing the accumulated number of seeds germinated at each time.

References

LABOURIAU LG; VALADARES MB. 1976. On the germination of seeds of *Calotropis procera*. *Anais da Academia Brasileira de Ciencias* 48:174-186. LIFCHITZ A. 1981. *Plantas medicinales*. 5. ed. Buenos Aires: Kier. 139p.

Examples

```
time <- c(1,2,3,4,5,6,7,8,9,10)
nger <- c(0,2,4,15,25,38,45,50,50,50)
Unc(time,nger)
```

UnifG

Germination Uniformity Index

Description

Calculates the Germination Uniformity Index (Sako, 2001).

Usage

```
UnifG(time,nger)
```

Arguments

time A vector object containing the time for germination.

nger A vector object containing the accumulated number of seeds germinated at each time.

References

SAKO, Y.; MCDONALD, M. B.; FUJIMURA, K.; EVANS, A. F.; BENNETT, M. A. A system for automated seed vigour assessment. *Seed Science and Technology*, v. 29, n. 3, p. 625-636, 2001.

Examples

```
time <- c(1,2,3,4,5,6,7,8,9,10)
nger <- c(0,2,4,15,25,38,45,50,50,50)
UnifG(time,nger)
```

unif_1	<i>Seedling Uniformity Index</i>
--------	----------------------------------

Description

It calculates the Seedling Uniformity Index (Sako, 2001).

Usage

```
unif_1(lengths)
```

Arguments

lengths	A data.frame object containing seedling lengths data with four columns. The first and second columns are for identification, e.g. treatments and repetitions. The third is the shoot length and the fourth is the root length.
---------	--

References

SAKO, Y.; MCDONALD, M. B.; FUJIMURA, K.; EVANS, A. F.; BENNETT, M. A. A system for automated seed vigour assessment. *Seed Science and Technology*, v. 29, n. 3, p. 625-636, 2001.

Examples

```
Seedling <- data.frame(  
  LOTE = c(1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 2),  
  REP = c(1, 1, 1, 1, 2, 2, 2, 1, 1, 1, 1, 2, 2, 2, 2),  
  SH = c(0.00, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 0.64, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 1.98),  
  ROOT = c(4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 8.75)  
)  
print(Seedling)  
Unif <- unif_1(Seedling)  
Unif
```

unif_2	<i>Seedling Uniformity Index</i>
--------	----------------------------------

Description

It calculates the Seedling Uniformity Index (Christiansen, 1942; adapted for Castan et al., 2018).

Usage

```
unif_2(lengths)
```

Arguments

`lengths` A `data.frame` object containing seedling lengths data with four columns. The first and second columns are for identification, e.g. treatments and repetitions. The third is the shoot length and the fourth is the root length.

References

CASTAN, D. O. C.; GOMES-JUNIOR, F. G.; MARCOS-FILHO, J. Vigor-S, a new system for evaluating the physiological potential of maize seeds. *Scientia Agricola*, v. 75, n. 2, p. 167-172, 2018.

Examples

```
Seedling <- data.frame(
  LOTE = c(1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 2),
  REP = c(1, 1, 1, 1, 2, 2, 2, 1, 1, 1, 1, 2, 2, 2, 2),
  SH = c(0.00, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 0.64, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 1.98),
  ROOT = c(4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 8.75)
)
print(Seedling)
Unif <- unif_2(Seedling)
Unif
```

 VarGer

Variance of Germination Time

Description

Calculates the Variance of Germination Time (Labouriau, 1983).

Usage

```
VarGer(time, nger)
```

Arguments

`time` A vector object containing the time for germination.

`nger` A vector object containing the accumulated number of seeds germinated at each time.

References

LABOURIAU, L. G. (1983). Uma nova linha de pesquisa na fisiologia da germinação das sementes. *Anais do XXXIV Congresso Nacional de Botânica*. SBB, Porto Alegre, 11-50.

Examples

```
time <- c(1,2,3,4,5,6,7,8,9,10)
nger <- c(0,2,4,15,25,38,45,50,50,50)
VarGer(time,nger)
```

vigor

*Seed Vigor Index***Description**

It calculates the Seed Vigor Index (Sako, 2001).

Usage

```
vigor(lengths, wg = 0.7, wu = 0.3, Unif = 1)
```

Arguments

lengths	A data.frame object containing seedling lengths data with four columns. The first and second columns are for identification, e.g. treatments and repetitions. The third is the shoot length and the fourth is the root length.
wg	A numeric value between zero and one. Default is 0.7. Is the weight given to the seedling length in the Vigor index calculation.
wu	A numeric value between zero and one. Default is 0.3. Is the weight given to the Unif_2 index calculation.
Unif	A numeric value, 1 or 2. If 1, the unif_1 index is used for vigor index calculation. If 2, the Unif_2 index is used for Vigor index calculation.

References

SAKO, Y.; MCDONALD, M. B.; FUJIMURA, K.; EVANS, A. F.; BENNETT, M. A. A system for automated seed vigour assessment. *Seed Science and Technology*, v. 29, n. 3, p. 625-636, 2001.

Examples

```
Seedling <- data.frame(
  LOTE = c(1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2, 2),
  REP = c(1, 1, 1, 1, 2, 2, 2, 1, 1, 1, 1, 2, 2, 2, 2),
  SH = c(0.00, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 0.64, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 1.98),
  ROOT = c(4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 8.75)
)
print(Seedling)
VigInd <- vigor(Seedling, wg = 0.7, wu = 0.3, Unif = 1)
VigInd
```

vigor_corr	<i>Seed Corrected Vigor Index</i>
------------	-----------------------------------

Description

It calculates the Seed Corrected Vigor Index (Medeiros & Pereira, 2018).

Usage

```
vigor_corr(lengths, Ger = 100, wg = 0.7, wu = 0.3, Unif = 1)
```

Arguments

lengths	A data.frame object containing seedling lengths data with four columns. The first and second columns are for identification, e.g. treatments and repetitions. The third is the shoot length and the fourth is the root length.
Ger	A data.frame object containing two columns. The first must contain the identification of the treatments identical to the first column of the seedling length data. The default is the numeric value 100 and in this case the vigor_corr is equal to vigor index.
wg	A numeric value between zero and one. Default is 0.7. Is the weight given to the seedling length in the Vigor index calculation.
wu	A numeric value between zero and one. Default is 0.3. Is the weight given to the Unif_2 index calculation.
Unif	A numeric value, 1 or 2. If 1, the unif_1 index is used for vigor index calculation. If 2, the Unif_2 index is used for Vigor index calculation.

References

MEDEIROS, A. D. DE; PEREIRA, M. D. SAPL: a free software for determining the physiological potential in soybean seeds. *Pesquisa Agropecuaria Tropical*, v. 48, n. 3, p. 222-228, 2018.

Examples

```
Seedling <- data.frame(
  LOTE = c(1, 1, 1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 2, 2),
  REP = c(1, 1, 1, 1, 2, 2, 2, 1, 1, 1, 1, 2, 2, 2),
  SH = c(0.00, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 0.64, 2.77, 1.18, 1.07, 0.80, 2.65, 3.51, 1.98),
  ROOT = c(4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 4.86, 6.71, 7.88, 3.68, 9.68, 8.88, 9.85, 8.75)
)
print(Seedling)

Ger <- data.frame(LOTE = c(1,2), GER = (c(90,80)))
print(Ger)

VigInd <- vigor_corr(Seedling, Ger, wg = 0.7, wu = 0.3, Unif = 1)
VigInd
```

Index

* indexes

GermCalc, [5](#)

PlantCalc, [11](#)

* package

SeedCalc-package, [2](#)

CVG, [3](#)

CVt, [4](#)

FGP, [4](#)

GermCalc, [5](#)

growth, [6](#)

GSI, [7](#)

mean_pa, [7](#)

mean_raiz, [8](#)

mean_razao, [9](#)

mean_total, [9](#)

MGR, [10](#)

MGT, [11](#)

PlantCalc, [11](#)

SeedCalc (SeedCalc-package), [2](#)

SeedCalc-package, [2](#)

Sinc, [13](#)

T10, [13](#)

T50, [14](#)

T90, [15](#)

Unc, [15](#)

unif_1, [17](#)

unif_2, [17](#)

UnifG, [16](#)

VarGer, [18](#)

vigor, [19](#)

vigor_corr, [20](#)