

Package ‘codecountR’

October 16, 2024

Title Counting Codes in a Text and Preparing Data for Analysis

Version 0.0.4.5

Description Data analysis often requires coding, especially when data are collected through interviews, observations, or questionnaires. As a result, code counting and data preparation are essential steps in the analysis process. Analysts may need to count the codes in a text (tokenization and counting of pre-established codes) and prepare the data (e.g., min-max normalization, Z-score, robust scaling, Box-Cox transformation, and non-parametric bootstrap). For the Box-Cox transformation (Box & Cox, 1964, <<https://www.jstor.org/stable/2984418>>), the optimal Lambda is determined using the log-likelihood method. Non-parametric bootstrap involves randomly sampling data with replacement. Two random number generators are also integrated: a Lehmer congruential generator for uniform distribution and a Box-Muller generator for normal distribution. Package for educational purposes.

License GPL-3

Encoding UTF-8

RoxygenNote 7.2.3

Imports stats

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Philippe Cohard [aut, cre]

Maintainer Philippe Cohard <p.cohard@laposte.net>

Repository CRAN

Date/Publication 2024-10-16 08:10:02 UTC

Contents

analysCodesList	2
bootStrap	3
BoxAndCox	3
BoxMullerGen	4
codeCount	5

congruGen	5
loadCodes	6
normMinMax	6
robustScal	7
subCalcBoxAndCox	8
tokenization	8
zScore	9

Index	10
--------------	-----------

analysCodesList	<i>analysCodesList</i>
-----------------	------------------------

Description

analysCodesList

Usage

```
analysCodesList(dataS, codesLis)
```

Arguments

dataS a character

codesLis a character

Value

a list

Examples

```
codes=list("@essai@", "@test@")
data = "this is an example @essai@, a bit long @essai@ text"
Result=analysCodesList(data,codes)
Result
```

bootStrap	<i>bootStrap</i>
-----------	------------------

Description

bootStrap

Usage

bootStrap(nameDframe, grpSize)

Arguments

nameDframe	a data.frame
grpSize	a number

Value

a matrix

Examples

```
j=c(10,14,56,30,58,78,99,1)
k=c(10,12,14,16,18,20,22,24)
x=data.frame(j,k)
res=bootStrap(x,5)
res
```

BoxAndCox	<i>BoxAndCox</i>
-----------	------------------

Description

BoxAndCox

Usage

BoxAndCox(rawVect, minLambda)

Arguments

rawVect	a vector
minLambda	a number

Value

a list

Examples

```
vec=rlnorm(100, log(3), log(3))
BandC=BoxAndCox(vec, -3)
BandC
BAC=unlist(BandC$par)
BAC
rawVectBCFinal=unlist(subCalcBoxAndCox(vec, BandC$par))
```

 BoxMullerGen

BoxMullerGen

Description

BoxMullerGen

Usage

```
BoxMullerGen(r, s)
```

Arguments

r	a number
s	a number

Value

a vector

Examples

```
#with runif
v=BoxMullerGen(runif(1), runif(1))
print(v)
```

```
#with congruGen
seed = 123456789
X=c()
for(i in 1: 2) {
  Z=congruGen(seed)
  seed=Z$seedUpdate
  X=append(X, Z$aleaNum)
}
#print(X)
```

```
N=BoxMullerGen(X[1], X[2])
print(N[1])
print(N[2])
```

codeCount	<i>codeCount</i>
-----------	------------------

Description

codeCount

Usage

```
codeCount(dataSet, code)
```

Arguments

dataSet	a character
code	a character

Value

a number

Examples

```
data = "this is an example @essai@"  
codeCount(data, "@essai@") #number of lines containing the chain
```

congruGen	<i>congruGen</i>
-----------	------------------

Description

congruGen

Usage

```
congruGen(seed, a)
```

Arguments

seed	a number
a	a number

Value

a list

Examples

```

seed = 123456789
for(i in 1: 10) {
  Z=congruGen(seed)
  seed=Z$seedUpdate
  num=Z$aaleaNum
  print(num)
}

```

loadCodes

loadCodes

Description

loadCodes

Usage

```
loadCodes(txtFile)
```

Arguments

txtFile a character

Value

a list

Examples

```

theFile =system.file("codesList.txt", package = "codecountR")
data=loadCodes(theFile)

```

normMinMax

normMinMax

Description

normMinMax

Usage

```
normMinMax(nameDframe)
```

Arguments

nameDframe a data.frame

Value

a data.frame

Examples

```
j=c(10,14,56,30,58,78,99,1)
k=c(10,12,14,16,18,20,22,24)
x=data.frame(j,k)
xMinMax=normMinMax(x)
xMinMax
```

robustScal	<i>robustScal</i>
------------	-------------------

Description

robustScal

Usage

```
robustScal(nameDframe)
```

Arguments

nameDframe a data.frame

Value

a data.frame

Examples

```
j=c(10,14,56,30,58,78,99,1)
k=c(10,12,14,16,18,20,22,24)
x=data.frame(j,k)
xRsc=robustScal(x)
xRsc
```

subCalcBoxAndCox *subCalcBoxAndCox*

Description

subCalcBoxAndCox

Usage

```
subCalcBoxAndCox(sortedVect, actualLambda)
```

Arguments

sortedVect a vector
actualLambda a number

Value

a vector

Examples

```
vec=rlnorm(100, log(3), log(3))  
BandC=subCalcBoxAndCox(vec, -3)
```

tokenization *tokenization*

Description

tokenization

Usage

```
tokenization(txtFile)
```

Arguments

txtFile a character

Value

a list

Examples

```
theFile =system.file("ExText.txt", package = "codecountR")  
data=tokenization(theFile)
```

zScore	<i>zScore</i>
--------	---------------

Description

zScore

Usage

zScore(namedDframe)

Arguments

namedDframe a data.frame

Value

a data.frame

Examples

```
j=c(10,14,56,30,58,78,99,1)
k=c(10,12,14,16,18,20,22,24)
x=data.frame(j,k)
xZsc=zScore(x)
xZsc
```

Index

analysCodesList, 2

bootStrap, 3
BoxAndCox, 3
BoxMullerGen, 4

codeCount, 5
congruGen, 5

loadCodes, 6

normMinMax, 6

robustScal, 7

subCalcBoxAndCox, 8

tokenization, 8

zScore, 9