

Package ‘nnls’

October 23, 2024

Type Package

Title The Lawson-Hanson Algorithm for Non-Negative Least Squares (NNLS)

Version 1.6

Maintainer Katharine Mullen <mullenkate@gmail.com>

Suggests bvlr, quadprog

Description An R interface to the Lawson-Hanson implementation of an algorithm for non-negative least squares (NNLS). Also allows the combination of non-negative and non-positive constraints.

License GPL (>= 2)

NeedsCompilation yes

Author Katharine M. Mullen [aut],
Ivo H. M. van Stokkum [aut],
Katharine Mullen [cre]

Repository CRAN

Date/Publication 2024-10-23 06:30:02 UTC

Contents

nnls-package	1
nnls	2
nnpls	5

Index	9
--------------	----------

nnls-package	<i>The Lawson-Hanson NNLS implementation of non-negative least squares</i>
--------------	--

Description

An R interface to the Lawson-Hanson NNLS implementation of an algorithm for non-negative linear least squares that solves the least squares problem $\min \|Ax = b\|_2$ with the constraint $x \geq 0$ where $x \in R^n$, $b \in R^m$ and A is an $m \times n$ matrix. Also allows the combination of non-negative and non-positive constraints on x .

References

Lawson CL, Hanson RJ (1974). Solving Least Squares Problems. Prentice Hall, Englewood Cliffs, NJ.

Lawson CL, Hanson RJ (1995). Solving Least Squares Problems. Classics in Applied Mathematics. SIAM, Philadelphia.

See Also

[nnls](#), [nnmpls](#), the method "L-BFGS-B" for [optim](#), [solve.QP](#), [bvls](#)

nnls	<i>The Lawson-Hanson NNLS implementation of non-negative least squares</i>
------	--

Description

An R interface to the Lawson-Hanson NNLS implementation of an algorithm for non-negative linear least squares that solves $\min \|Ax - b\|_2$ with the constraint $x \geq 0$, where $x \in R^n$, $b \in R^m$ and A is an $m \times n$ matrix.

Usage

```
nnls(A, b)
```

Arguments

A	numeric matrix with m rows and n columns
b	numeric vector of length m

Value

nnls returns an object of class "nnls".

The generic accessor functions `coefficients`, `fitted.values`, `deviance` and `residuals` extract various useful features of the value returned by `nnls`.

An object of class "nnls" is a list containing the following components:

x	the parameter estimates.
deviance	the residual sum-of-squares.
residuals	the residuals, that is response minus fitted values.

fitted	the fitted values.
mode	a character vector containing a message regarding why termination occurred.
passive	vector of the indices of x that are not bound at zero.
bound	vector of the indices of x that are bound at zero.
nsetp	the number of elements of x that are not bound at zero.

Source

This is an R interface to the Fortran77 code distributed with the book referenced below by Lawson CL, Hanson RJ (1995), obtained from Netlib (file 'lawson-hanson/all'), with a trivial modification to return the variable NSETP.

References

Lawson CL, Hanson RJ (1974). Solving Least Squares Problems. Prentice Hall, Englewood Cliffs, NJ.

Lawson CL, Hanson RJ (1995). Solving Least Squares Problems. Classics in Applied Mathematics. SIAM, Philadelphia.

See Also

[nnnpls](#), the method "L-BFGS-B" for [optim](#), [solve.QP](#), [bvls](#)

Examples

```
## simulate a matrix A
## with 3 columns, each containing an exponential decay
t <- seq(0, 2, by = .04)
k <- c(.5, .6, 1)
A <- matrix(nrow = 51, ncol = 3)
Acolfunc <- function(k, t) exp(-k*t)
for(i in 1:3) A[,i] <- Acolfunc(k[i],t)

## simulate a matrix X
## with 3 columns, each containing a Gaussian shape
## the Gaussian shapes are non-negative
X <- matrix(nrow = 51, ncol = 3)
wavenum <- seq(18000,28000, by=200)
location <- c(25000, 22000, 20000)
delta <- c(3000,3000,3000)
Xcolfunc <- function(wavenum, location, delta)
  exp( - log(2) * (2 * (wavenum - location)/delta)^2)
for(i in 1:3) X[,i] <- Xcolfunc(wavenum, location[i], delta[i])

## set seed for reproducibility
set.seed(3300)

## simulated data is the product of A and X with some
## spherical Gaussian noise added
matdat <- A %*% t(X) + .005 * rnorm(nrow(A) * nrow(X))
```



```

# X_quadprog <- quadprog_sol(matdat,A)

## the RMS deviation under NNLS is about the same as under quadprog
# sqrt(sum((X - X_nnls)^2))
# sqrt(sum((X - X_quadprog)^2))

## and quadprog requires about the same amount of time
# system.time(nnls_sol(matdat,A))
# system.time(quadprog_sol(matdat,A))

## End(Not run)

```

nnnpls	<i>An implementation of least squares with non-negative and non-positive constraints</i>
--------	--

Description

An implementation of an algorithm for linear least squares problems with non-negative and non-positive constraints based on the Lawson-Hanson NNLS algorithm. Solves $\min \|Ax - b\|_2$ with the constraint $x_i \geq 0$ if $con_i \geq 0$ and $x_i \leq 0$ otherwise, where $x, con \in R^n$, $b \in R^m$, and A is an $m \times n$ matrix.

Usage

```
nnnpls(A, b, con)
```

Arguments

A	numeric matrix with m rows and n columns
b	numeric vector of length m
con	numeric vector of length m where element i is negative if and only if element i of the solution vector x should be constrained to non-positive, as opposed to non-negative, values.

Value

nnnpls returns an object of class "nnnpls".

The generic accessor functions `coefficients`, `fitted.values`, `deviance` and `residuals` extract various useful features of the value returned by `nnnpls`.

An object of class "nnnpls" is a list containing the following components:

x	the parameter estimates.
deviance	the residual sum-of-squares.
residuals	the residuals, that is response minus fitted values.

fitted	the fitted values.
mode	a character vector containing a message regarding why termination occurred.
passive	vector of the indices of x that are not bound at zero.
bound	vector of the indices of x that are bound at zero.
nsetp	the number of elements of x that are not bound at zero.

Source

This is an R interface to Fortran77 code distributed with the book referenced below by Lawson CL, Hanson RJ (1995), obtained from Netlib (file 'lawson-hanson/all'), with some trivial modifications to allow for the combination of constraints to non-negative and non-positive values, and to return the variable NSETP.

References

- Lawson CL, Hanson RJ (1974). Solving Least Squares Problems. Prentice Hall, Englewood Cliffs, NJ.
- Lawson CL, Hanson RJ (1995). Solving Least Squares Problems. Classics in Applied Mathematics. SIAM, Philadelphia.

See Also

[nnls](#), the method "L-BFGS-B" for [optim](#), [solve.QP](#), [bvls](#)

Examples

```
## simulate a matrix A
## with 3 columns, each containing an exponential decay
t <- seq(0, 2, by = .04)
k <- c(.5, .6, 1)
A <- matrix(nrow = 51, ncol = 3)
Acolfunc <- function(k, t) exp(-k*t)
for(i in 1:3) A[,i] <- Acolfunc(k[i],t)

## simulate a matrix X
## with 3 columns, each containing a Gaussian shape
## 2 of the Gaussian shapes are non-negative and 1 is non-positive
X <- matrix(nrow = 51, ncol = 3)
wavenum <- seq(18000,28000, by=200)
location <- c(25000, 22000, 20000)
delta <- c(3000,3000,3000)
Xcolfunc <- function(wavenum, location, delta)
  exp( - log(2) * (2 * (wavenum - location)/delta)^2)
for(i in 1:3) X[,i] <- Xcolfunc(wavenum, location[i], delta[i])
X[,2] <- -X[,2]

## set seed for reproducibility
set.seed(3300)

## simulated data is the product of A and X with some
```



```
# }
# X_quadprog <- quadprog_sol(matdat,A)

## the RMS deviation under NNNPLS is about the same as under quadprog
# sqrt(sum((X - X_nnnpls)^2))
# sqrt(sum((X - X_quadprog)^2))

## and quadprog requires about the same amount of time
# system.time(nnnpls_sol(matdat,A))
# system.time(quadprog_sol(matdat,A))

## End(Not run)
```


Index

* **optimize**

nnls, [2](#)

nnnpls, [5](#)

* **package**

nnls-package, [1](#)

bvls, [2](#), [3](#), [6](#)

nnls, [2](#), [2](#), [6](#)

nnls-package, [1](#)

nnnpls, [2](#), [3](#), [5](#)

optim, [2](#), [3](#), [6](#)

solve.QP, [2](#), [3](#), [6](#)