

Package ‘synlik’

March 2, 2023

Type Package

Title Synthetic Likelihood Methods for Intractable Likelihoods

Version 0.1.6

Date 2023-03-02

Author Matteo Fasiolo and Simon Wood

Maintainer Matteo Fasiolo <matteo.fasiolo@gmail.com>

Description Framework to perform synthetic likelihood inference for models where the likelihood function is unavailable or intractable.

URL http://mfasiolo.github.io/synlik_release/

License GPL (>= 2)

Depends R (>= 2.10), Rcpp (>= 0.12.0)

Imports methods, graphics, Matrix, compiler, stats, parallel

Suggests knitr, markdown, stabledist

LinkingTo Rcpp, RcppArmadillo

VignetteBuilder knitr

RoxygenNote 5.0.1

NeedsCompilation yes

Repository CRAN

Date/Publication 2023-03-02 14:10:02 UTC

R topics documented:

synlik-package	2
ANYOrNULL-class	4
bf	5
blowSimul	6
blow_sl	7
checkNorm	8
continue	10

extractCorr	11
functionOrNULL-class	11
internal_C	12
nlar	12
numericOrNULL-class	13
orderDist	13
plot-smcmc	14
plot-synlik	15
rickerSimul	16
ricker_sl	18
robCov	19
simulate,synlik-method	20
slAcf	21
slice	22
slik	23
smcmc	24
smcmc-class	25
synlik-class	27

Index	29
--------------	-----------

synlik-package

Synthetic Likelihood Methods for Intractable Likelihoods

Description

Package that provides Synthetic Likelihood methods for intractable likelihoods. The package is meant to be as general purpose as possible: as long as you are able to simulate data from your model you should be able to fit it.

Details

Package: synlik
 Type: Package
 Version: 0.1.2
 Date: 2018-05-22
 License: GPL (>=2)

The package allows users to create objects of class `synlik` (S4), which are essentially constituted of a simulator function and a function (`summaries`) that transforms the data into summary statistics. The simulator can output any kind of data (vector, list, etc) and this will be passed directly to the `summaries` function. This allow the package to fit a large variety of models.

Once the model of interest has been set up as a `synlik` object, it is possible several methods on it. The function most useful function is `slik`, which can be used to evaluate the synthetic likelihood. The `slice.synlik` function allows to obtain and plot slices of the synthetic likelihood with respect

to model parameters. It is possible to simulate data or statistics from the model using the generic `simulate`, and to check the normality of the statistics using the `checkNorm` function. Unknown parameters can be estimated by MCMC, through the `smcmc` function. This function will return an object of class `smcmc` (S4), which contains all the inputs and results of the MCMC procedure.

Many functions in the package support parallel simulation on multiple cores.

Author(s)

Matteo Fasiolo and Simon N. Wood

Maintainer: Matteo Fasiolo <matteo.fasiolo@gmail.com>

References

Simon N Wood. Statistical inference for noisy nonlinear ecological dynamic systems. *Nature*, 466(7310):1102–1104, 2010.

See Also

For some examples see the Vignettes (type `vignette("synlik")`).

Examples

```
## Not run:
#### Here I put a simple example,
#### if you want to see more type: vignette("synlik")

## End(Not run)

#### Create synlik object
ricker_sl <- synlik(simulator = rickerSimul,
                  summaries = rickerStats,
                  param = c(logR = 3.8, logSigma = log(0.3), logPhi = log(10)),
                  extraArgs = list("nObs" = 50, "nBurn" = 50),
                  plotFun = function(input, ...){
                    plot(drop(input), type = 'l', ylab = "Pop", xlab = "Time", ...)
                  }
)

#### Simulate from the object
ricker_sl@data <- simulate(ricker_sl)
ricker_sl@extraArgs$obsData <- ricker_sl@data

#### Simulate statistics (each row is a vector of statistics)
simulate(ricker_sl, seed = 523, nsim = 10, stats = TRUE)

#### Plotting the data
plot(ricker_sl)

#### Checking multivariate normality of the statistics
```

```

checkNorm(ricker_sl)

#### Evaluate the likelihood
set.seed(4234)
slik(ricker_sl,
     param = c(logR = 3.8, logSigma = log(0.3), logPhi = log(10)),
     nsim   = 1e3)

#### Plotting a slice of the log-Likelihood possibly using multiple cores
slice(object = ricker_sl,
      ranges = list("logR" = seq(3.5, 3.9, by = 0.02),
                   "logPhi" = seq(2, 2.6, by = 0.02),
                   "logSigma" = seq(-2, -0.5, by = 0.05)),
      param = c(logR = 3.8, logSigma = log(0.3), logPhi = log(10)),
      nsim = 500, multicore = FALSE)

#### MCMC estimation possibly using multiple cores
set.seed(4235)
ricker_sl <- smcmc(ricker_sl,
                  initPar = c(3.2, -1, 2.6),
                  niter = 50,
                  burn = 3,
                  priorFun = function(input, ...) 0,
                  propCov = diag(c(0.1, 0.1, 0.1))^2,
                  nsim = 1e3,
                  multicore = FALSE)

# Continue with additional 50 iterations
ricker_sl <- continue(ricker_sl, niter = 50)

# Plotting results on transformed scale (exponential)
trans <- rep("exp", 3)
names(trans) <- names(ricker_sl@param)

plot(ricker_sl)

```

ANYOrNULL-class

Dummy class

Description

Class unions for internal use only

bf

Nicholson's 1954 blowfly data

Description

Data from figures 3 and 4 of Nicholson, 1954.

Usage

data(bf1)

Arguments

bf1 the dataset name

Details

bf1 is Nisbet and Gurney's run 1, and Nicholson's (1954) figure 3 (adult food limitation). The data are actually from the global population dynamics database at Silwood. They are daily: Nicholson's figure 3 plots data every other day, but the text says that measurements were taken daily. However elsewhere they are reported every other day. Probably best to assume that they have been interpolated to daily.

bf2 and bf3 are digitized from Nicholson's (1954) figure 4. bf2 is the upper series: larval food limitation, with 50g per day of larval food provided. bf3 is the lower series: same set up, half as much food. These are Nisbet and Gurney's runs 2 and 3, respectively.

Value

matrix of replicate data series

Author(s)

Simon N. Wood, maintainer Matteo Fasiolo <matteo.fasiolo@@gmail.com>

References

Alexander J Nicholson. An outline of the dynamics of animal populations. Australian Journal of Zoology, 2(1):9–65, 1954.

See Also

blowfly

Examples

```

library(synlik)
data(bf1)
data(bf2)
data(bf3)
par(mfrow=c(3,1),mar=c(4,4,1,1))
with(bf1,plot(day,pop,type="l"))
with(bf1,points(day,pop,pch=20,cex=.8))
abline(mean(bf1$pop),0,col=2); abline(median(bf1$pop),0,col=3);
with(bf2,plot(day,pop,type="l"))
with(bf2,points(day,pop,pch=20,cex=.8))
abline(mean(bf2$pop),0,col=2); abline(median(bf2$pop),0,col=3);
with(bf3,plot(day,pop,type="l"))
with(bf3,points(day,pop,pch=20,cex=.8))
abline(mean(bf3$pop),0,col=2); abline(median(bf3$pop),0,col=3);

```

blowSimul

*Simulates from the blowfly model***Description**

Simulator for the blowfly model proposed by Wood (2010).

Usage

```
blowSimul(param, nsim, extraArgs, ...)
```

Arguments

param	vector of log-parameters: delta, P, N0, var.p, tau and var.d. The interpretation of these parameters is described in Wood (2010).
nsim	Number of simulations from the model.
extraArgs	A named list of additional arguments: <ul style="list-style-type: none"> • nObs = Length of each simulated time series. • nBurn = Number of initial steps to be discarded before saving the following nObs steps. • steps = Positive integer. If steps == n the observations correspond to n time steps.
...	Need for compatibility with synlik, but not used.

Value

A matrix nsim by nObs, where each row is a simulated path.

Author(s)

Simon Wood and Matteo Fasiolo <matteo.fasiolo@gmail.com>.

References

Simon N Wood. Statistical inference for noisy nonlinear ecological dynamic systems. *Nature*, 466(7310):1102–1104, 2010.

Brillinger, D. R., J. Guckenheimer, P. Guttorp, and G. Oster. 1980. Empirical modelling of population time series data: the case of age and density dependent vital rates. *Lectures on Mathematics in the Life Sciences*13:65-90.

Nicholson, A. J. 1957. The self-adjustment of populations to change. *Cold Spring Harbor Symposia on Quantitative Biology*22:153-173.

See Also

[blow_sl](#)

Examples

```
tmp <- blowSimul(param = log( c( "delta" = 0.16, "P" = 6.5, "N0" = 400,
                               "var.p" = 0.1, "tau" = 14, "var.d" = 0.1) ),
                nsim = 2,
                extraArgs = list("nObs" = 200, "nBurn" = 1000, "steps" = 2))
matplot(t(tmp), type = 'l', ylab = "Y", xlab = "Time")
```

blow_sl

Blowfly model

Description

synlik object containing the blowfly model proposed by Wood (2010). The main components are the simulator [blowSimul](#) and the statistics [blowStats](#), described in the same reference.

Author(s)

Simon Wood and Matteo Fasiolo <matteo.fasiolo@gmail.com>.

References

Simon N Wood. Statistical inference for noisy nonlinear ecological dynamic systems. *Nature*, 466(7310):1102–1104, 2010.

See Also

[blowSimul](#)

Examples

```

data(blow_sl)

plot(blow_sl)
simulate(blow_sl, stats = TRUE)

slik(blow_sl,
     param = log( c( "delta" = 0.16, "P" = 6.5, "N0" = 400,
                    "var.p" = 0.1, "tau" = 14, "var.d" = 0.1) ),
     nsim   = 1e3)

# Using Nicholson's data
data(bf1)

plot(blow_sl)

blow_sl@data <- bf1$pop
blow_sl@extraArgs$obsData <- bf1$pop #Important: blow_sl@blowStats uses the observed data

slik(blow_sl,
     param = log( c( "delta" = 0.16, "P" = 6.5, "N0" = 400,
                    "var.p" = 0.1, "tau" = 14, "var.d" = 0.1) ),
     nsim   = 1e3)

```

checkNorm

*Checking the multivariate normal approximation.***Description**

Given an object of class `synlik` this routine provides a graphical check of whether the distribution of the random summary statistics is multivariate normal.

Usage

```

checkNorm(object, param = object@param, nsim = 1000, observed = NULL,
          cex.axis = 1, cex.lab = 1, ...)

```

Arguments

<code>object</code>	An object of class <code>synlik</code> or a matrix where each row is a random vector.
<code>param</code>	A vector of model's parameters at which the summary statistics will be simulated.
<code>nsim</code>	number of summary statistics to be simulated if object is of class <code>synlik</code> , otherwise it is not used.
<code>observed</code>	A vector of observed summary statistics. By default <code>NULL</code> , so <code>object@data</code> will be used as observed statistics. It will be looked at only if object is a matrix.
<code>cex.axis</code>	Axis scale expansion factor.

cex.lab	Axis label expansion factor.
...	additional arguments to be passed to <code>object@simulator</code> and <code>object@summaries</code> . In general I would avoid using it and including in <code>object@extraArgs</code> everything they need.

Details

The method is from section 7.5 of Krzanowski (1988). The replicate vectors of summary statistic S are transformed to variables which should be univariate chi squared r.v.s with DoF given by the number of rows of S . An appropriate QQ-plot is produced, and the proportion of the data differing substantially from the ideal line is reported. Deviations at the right hand end of the plot indicate that the tail behaviour of the Normal approximation is poor: in the context of synthetic likelihood this is of little consequence. Secondly, s is transformed to a vector which should be i.i.d. $N(0,1)$ under multivariate normality, and a QQ plot is produced. Unfortunately this approach is not very useful unless the dimension of s is rather large. In simulations, perfectly MVN data produce highly variable results, so that the approach lacks any real power.

Value

Mainly produces plots and prints output. Also an array indicating proportion of simulated statistics smaller than observed.

Author(s)

Simon N. Wood, maintained by Matteo Fasiolo <matteo.fasiolo@gmail.com>.

References

Krzanowski, W.J. (1988) Principles of Multivariate Analysis. Oxford.

Examples

```
#### Create Object
data(ricker_sl)

#### Simulate from the object
ricker_sl@data <- simulate(ricker_sl)
ricker_sl@extraArgs$obsData <- ricker_sl@data

#### Checking multivariate normality
checkNorm(ricker_sl)

# With matrix input
checkNorm(matrix(rnorm(200), 100, 2))
```

continue	<i>Continuing estimation.</i>
----------	-------------------------------

Description

Generic function, that given the results of an estimation procedure (ex. MCMC or maximum likelihood optimization) continues the procedure for some more iterations.

Usage

```
continue(object, ...)

## S4 method for signature 'smcmc'
continue(object, niter = object@niter, nsim = object@nsim,
  propCov = object@propCov, targetRate = object@targetRate,
  recompute = object@recompute, multicore = object@multicore,
  ncores = object@ncores, cluster = NULL, control = object@control, ...)
```

Arguments

object	An object representing the results of an estimation procedure which we wish to continue. For example it might represents an MCMC chain.
...	additional arguments to be passed to <code>slik</code> function, see slik .
niter	see smcmc-class .
nsim	see smcmc-class .
propCov	see smcmc-class .
targetRate	see smcmc-class .
recompute	see smcmc-class .
multicore	see smcmc-class .
ncores	see smcmc-class .
cluster	an object of class <code>c("SOCKcluster", "cluster")</code> . This allows the user to pass her own cluster, which will be used if <code>multicore == TRUE</code> . The user has to remember to stop the cluster.
control	see smcmc-class .

Details

When `is("smcmc", object) == TRUE` continues MCMC estimation of an object of class `smcmc`. All input parameters are defaulted to the corresponding slots in the input object, with the exception of cluster. The chain restarts were it ended, burn-in is set to zero, the same prior (if any) is used.

Value

An object of the same class as `object`, where the results of the estimation have been updated.

See Also

For examples, see [smcmc-class](#).

extractCorr	<i>Extracting correlations from a covariance matrix</i>
-------------	---

Description

Extracting correlations from a covariance matrix

Usage

```
extractCorr(mat)
```

Arguments

mat A covariance matrix.

Value

The correlation matrix embedded in mat.

Examples

```
# 2 dimensional case
d <- 2
tmp <- matrix(rnorm(d^2), d, d)
mcov <- tcrossprod(tmp, tmp)

# Covariance matrix
mcov

# Correlation matrix
extractCorr(mcov)
```

functionOrNULL-class	<i>Dummy class</i>
----------------------	--------------------

Description

Class unions for internal use only

internal_C	<i>Internal C and C++ function</i>
------------	------------------------------------

Description

This functions are for internal use only.

Author(s)

Simon Wood and Matteo Fasiolo <matteo.fasiolo@gmail.com>.

nlar	<i>Estimate non-linear autoregressive coefficients</i>
------	--

Description

Function that, give time series data, transforms them into summary statistics using polynomial autoregression.

Usage

```
nlar(x, lag, power)
```

Arguments

x	a matrix. Each column contains a replicate series.
lag	vector of lags, for rhs terms.
power	vector of powers, for rhs terms.

Value

a matrix where each column contains the coefficients for a different replicate.

Author(s)

Simon N. Wood, maintainer Matteo Fasiolo <matteo.fasiolo@gmail.com>.

Examples

```

library(synlik)
set.seed(10)
x <- matrix(runif(200),100,2)
beta <- nlar(x,lag=c(1,1),power=c(1,2))
y <- x[,1]
y <- y - mean(y)
z <- y[1:99];y <- y[2:100]
lm(y~z+I(z^2)-1)
beta

## NA testing
x[5,1] <- x[45,2] <- NA
beta <- nlar(x,lag=c(1,1),power=c(1,2))
y <- x[,1]
y <- y - mean(y,na.rm=TRUE)
z <- y[1:99];y <- y[2:100]
lm(y~z+I(z^2)-1)
beta

## higher order...
set.seed(10)
x <- matrix(runif(100),100,2)
beta <- nlar(x,lag=c(6,6,6,1,1),power=c(1,2,3,1,2))
k <- 2
y <- x[,k]
y <- y - mean(y)
ind <- (1+6):100
y6 <- y[ind-6];y1 <- y[ind-1];y <- y[ind]
beta0 <- coef(lm(y~y6+I(y6^2)+I(y6^3)+y1+I(y1^2)-1))
as.numeric(beta[,k]);beta0;beta0-as.numeric(beta[,k])

```

numericOrNULL-class *Dummy class*

Description

Class unions for internal use only

orderDist *Summarize marginal distribution of (differenced) series.*

Description

Summarizes (difference) distribution of replicate series, by regressing ordered differenced series on a reference series (which might correspond to observed data).

Usage

```
orderDist(x, z, np = 3, diff = 1)
```

Arguments

x a matrix. Each column contains a replicate series.
z vector of lags, for rhs terms.
np maximum power on rhs of regression.
diff order of differencing (zero for none).

Value

a matrix where each column contains the coefficients for a different replicate.

Author(s)

Simon N. Wood, maintainer Matteo Fasiolo <matteo.fasiolo@gmail.com>.

Examples

```
library(synlik)
set.seed(10)
n <- 100;nr <- 3
x <- matrix(runif(n*nr),n,nr)
z <- runif(n)
beta <- orderDist(x,z,np=3,diff=1)

zd <- z;xd <- x[,3]
zd <- diff(zd,1);xd <- diff(xd,1)
zd <- sort(zd);zd <- zd - mean(zd)
xd <- sort(xd);xd <- xd - mean(xd)
lm(xd~zd+I(zd^2)+I(zd^3)-1)
```

plot-smcmc

Plotting objects of class smcmc.

Description

Method for plotting an object of class smcmc.

Usage

```
## S4 method for signature 'smcmc,missing'
plot(x, trans = NULL, addPlot1 = NULL,
     addPlot2 = NULL, ...)
```

Arguments

x	An object of class smcmc.
trans	Name list or vector containing names of transforms for some parameters (ex: <code>list("par1" = "exp", "par2" = "log")</code>). The transformations will be applied before plotting.
addPlot1	Name of additional plotting function that will be call after the MCMC chain have been plotted. It has to have prototype <code>fun(nam, ...)</code> where <code>nam</code> will be the parameter name. See "examples".
addPlot2	Name of additional plotting function that will be call after the histograms have been plotted. It has to have prototype <code>fun(nam, ...)</code> where <code>nam</code> will be the parameter name. See "examples".
...	additional arguments to be passed to the plotting functions.

See Also

[smcmc-class](#), [plot](#).

Examples

```
data(ricker_smcmc)

# Functions for additional annotations (true parameters)
addline1 <- function(parNam, ...){
  abline(h = exp(ricker_smcmc@param[parNam]), lwd = 2, lty = 2, col = 3)
}
addline2 <- function(parNam, ...){
  abline(v = exp(ricker_smcmc@param[parNam]), lwd = 2, lty = 2, col = 3)
}

# Transformations (exponentials)
trans <- rep("exp", 3)
names(trans) <- names(ricker_smcmc@param)

plot(ricker_smcmc,
     trans = trans,
     addPlot1 = "addline1",
     addPlot2 = "addline2")
```

plot-synlik

Method for plotting an object of class synlik.

Description

It basically calls the slot `object@plotFun` with input `object@data`, if it has been provided by the user. Otherwise it tries to use the `plot(x = object@data, y, ...)` generic.

Usage

```
## S4 method for signature 'synlik,missing'
plot(x, y, ...)
```

Arguments

```
x          An object of class synlik.
y          Useless argument, only here for compatibility reasons.
...        additional arguments to be passed to object@plotFun.
```

Author(s)

Matteo Fasiolo <matteo.fasiolo@gmail.com>

See Also

[synlik-class](#), [plot](#).

Examples

```
data(ricker_sl)

# Using ricker_sl@plotFun
plot(ricker_sl)

# Using generic plot, doesn't work well because object@data is a matrix.
ricker_sl@plotFun <- NULL
plot(ricker_sl)
```

rickerSimul

Simulates from the ricker model

Description

Simulator for the stochastic Ricker model, as described by Wood (2010). The observations are $Y_t \sim \text{Pois}(\Phi * N_t)$, and the dynamics of the hidden state are given by $N_t = r * N_{t-1} * \exp(-N_{t-1} + e_t)$, where $e_t \sim N(0, \text{Sigma}^2)$.

Usage

```
rickerSimul(param, nsim, extraArgs, ...)
```


Arguments

param	vector of log-parameters: logR, logSigma, logPhi. Alternatively a matrix nsim by 3 were each row is a different parameter vector.
nsim	Number of simulations from the model.
extraArgs	A named list of additional arguments: <ul style="list-style-type: none"> • nObs = Length of each simulated time series. • nBurn = Number of initial steps to be discarded before saving the following nObs steps. • randInit = if TRUE (default) the initial state N0 is runif(0, 1), otherwise it is equal to extraArgs\$initVal. • initVal = initial value N0, used only if extraArgs\$randInit == TRUE.
...	Need for compatibility with synlik, but not used.

Value

A matrix nsim by nObs, where each row is a simulated path.

Author(s)

Simon Wood and Matteo Fasiolo <matteo.fasiolo@gmail.com>.

References

Simon N Wood. Statistical inference for noisy nonlinear ecological dynamic systems. Nature, 466(7310):1102–1104, 2010.

See Also

[ricker_sl](#)

Examples

```
tmp <- rickerSimul(c(3.8, -1.2, 2.3), nsim = 2, extraArgs = list("nObs" = 50, "nBurn" = 200))
matplot(t(tmp), type = 'l', ylab = "Y", xlab = "Time")

parMat <- rbind(c(3.8, -1.2, 2.3), # Chaotic
               c(2.5, -1.2, 2.3)) # Not Chaotic

par(mfrow = c(2, 1))
tmp <- rickerSimul(parMat, nsim = 2, extraArgs = list("nObs" = 50, "nBurn" = 200))
plot(tmp[1, ], type = 'l', ylab = "Y", xlab = "Time")
plot(tmp[2, ], type = 'l', ylab = "Y", xlab = "Time")
```

ricker_sl	<i>Ricker model</i>
-----------	---------------------

Description

ricker_sl is synlik object containing the stochastic Ricker model, ricker_smcmc is a smcmc object which also contains the results of some MCMC iterations. The model is described [rickerSimul](#) and in Wood (2010). The main components of the object are the simulator [rickerSimul](#) and the statistics rickerStats, described in the same reference.

Author(s)

Simon Wood and Matteo Fasiolo <matteo.fasiolo@gmail.com>.

References

Simon N Wood. Statistical inference for noisy nonlinear ecological dynamic systems. *Nature*, 466(7310):1102–1104, 2010.

See Also

[rickerSimul](#)

Examples

```
data(ricker_sl)

plot(ricker_sl)
simulate(ricker_sl, stats = TRUE)

slik(ricker_sl,
     param = c( logR = 3.8, logSigma = log(0.3), logPhi = log(10) ),
     nsim   = 1e3)

# Using Nicholson's data
data(ricker_smcmc)

plot(ricker_smcmc)
```

robCov	<i>Robust covariance matrix estimation</i>
--------	--

Description

Obtains a robust estimate of the covariance matrix of a sample of multivariate data, using Campbell's (1980) method as described on p231-235 of Krzanowski (1988).

Usage

```
robCov(sY, alpha = 2, beta = 1.25)
```

Arguments

sY	A matrix, where each column is a replicate observation on a multivariate r.v.
alpha	tuning parameter, see details.
beta	tuning parameter, see details.

Details

Campbell (1980) suggests an estimator of the covariance matrix which downweights observations at more than some Mahalanobis distance d_0 from the mean. d_0 is $\sqrt{\text{nrow}(sY) + \alpha} / \sqrt{2}$. Weights are one for observations with Mahalanobis distance, d , less than d_0 . Otherwise weights are $d_0 \cdot \exp(-.5 \cdot (d - d_0)^2 / \beta) / d$. The defaults are as recommended by Campbell. This routine also uses pre-conditioning to ensure good scaling and stable numerical calculations.

Value

A list where:

- E square root of the inverse covariance matrix. i.e. the inverse cov matrix is $t(E) \%* \% E$;
- l \log of the determinant of the covariance matrix;
- m The estimated mean;
- sd The estimated standard deviations of each variable.

Author(s)

Simon N. Wood, maintained by Matteo Fasiolo <matteo.fasiolo@gmail.com>.

References

Krzanowski, W.J. (1988) Principles of Multivariate Analysis. Oxford. Campbell, N.A. (1980) Robust procedures in multivariate analysis I: robust covariance estimation. JRSSC 29, 231-237.

Examples

```
p <- 5; n <- 100
Y <- matrix(runif(p*n), p, n)
robCov(Y)
```

 simulate,synlik-method

Simulate data or statistics from an object of class synlik.

Description

Simulate data or statistics from an object of class synlik.

Usage

```
## S4 method for signature 'synlik'
simulate(object, nsim, seed = NULL, param = object@param,
         stats = FALSE, clean = TRUE, verbose = TRUE, ...)
```

Arguments

object	An object of class synlik.
nsim	Number of simulations from the model.
seed	Random seed to be used. It is not passed to the simulator, but simply passed to <code>set.seed()</code> from within <code>simulate.synlik</code> .
param	Vector of parameters passed to <code>object@simulator</code> .
stats	If TRUE the function transforms the simulated data into statistics using <code>object@summaries</code> .
clean	If TRUE the function tries to clean the statistics from NaNs or non-finite values. Given that <code>object@summaries</code> has to return a numeric vector or a matrix where each row is a simulation, rows containing non-finite values will be discarded.
verbose	If TRUE the function will complain if, for instance, the simulations contain lots of non-finite values.
...	additional arguments to be passed to <code>object@simulator</code> and <code>object@summaries</code> . In general I would avoid using it and including <code>object@extraArgs</code> everything they need.

Value

If `stats == FALSE` the output will be that of `object@simulator`, which depends on the simulator used by the user. If `stats == TRUE` the output will be a matrix where each row is a vector of simulated summary statistics.

Author(s)

Matteo Fasiolo <matteo.fasiolo@gmail.com>

See Also

[synlik-class](#), [simulate](#).

Examples

```
data(ricker_sl)

# Simulate data
simulate(ricker_sl, nsim = 2)

# Simulate statistics
simulate(ricker_sl, nsim = 2, stats = TRUE)
```

slAcf*Estimate auto-covariances for multiple datasets.*

Description

Function that, give time series data, transforms them into auto-covariances with different lags.

Usage

```
slAcf(x, max.lag = 10)
```

Arguments

x a matrix. Each column contains a replicate series.
max.lag How many lags to use.

Value

a matrix where each column contains the coefficients for a different replicate. The first coefficient corresponds to lag == 0, hence it is the variance, the second is the covariance one step ahead and so on.

Author(s)

Simon N. Wood, maintainer Matteo Fasiolo <matteo.fasiolo@gmail.com>.

Examples

```
library(synlik)
set.seed(10)
x <- matrix(runif(1000),100,10)
acf <- slAcf(x)
```

slice *Plot slices of the synthetic log-likelihood.*

Description

Plot slices of the synthetic log-likelihood.

Usage

```
slice(object, ranges, nsim, param = object@param, pairs = FALSE,
      draw = TRUE, trans = NULL, multicore = FALSE, ncores = detectCores() -
      1, cluster = NULL, ...)
```

Arguments

object	synlik object.
ranges	ranges of values along which we want the slices. If <code>length(parName) == 1</code> than range has a vector, while if <code>length(parName) == 2</code> it have to be a named list of 2 vectors (ex: <code>list("alpha" = 1:10, "beta" = 10:1)</code>).
nsim	Number of simulations used to evaluate the synthetic likelihood at each location.
param	Named vector containing the value of the ALL parameters (including the sliced one). Parameters that are not in <code>parName</code> will be fixed to the values in <code>param</code> .
pairs	if TRUE the function will produce a 2D slice for every pair of parameters in <code>ranges</code> . FALSE by default.
draw	If TRUE the slice will be plotted.
trans	Named vector or list of transformations to be applied to the parameters in <code>parName</code> before plotting ex: <code>trans = c(s = "exp", d = "exp")/</code>
multicore	If TRUE the <code>object@simulator</code> and <code>object@summaries</code> functions will be executed in parallel. That is the <code>nsim</code> simulations will be divided in multiple cores.
ncores	Number of cores to use if <code>multicore == TRUE</code> .
cluster	An object of class <code>c("SOCKcluster", "cluster")</code> . This allows the user to pass her own cluster, which will be used if <code>multicore == TRUE</code> . The user has to remember to stop the cluster.
...	additional arguments to be passed to <code>slik()</code> , see slik .

Value

Either a vector or matrix of log-synthetic likelihood estimates, depending on whether `length(parNames) == 1` or `2`. These are returned invisibly.

Author(s)

Matteo Fasiolo <matteo.fasiolo@gmail.com>

Examples

```

data(ricker_sl)

# Plotting slices of the logLikelihood
slice(object = ricker_sl,
      ranges = list("logR" = seq(3.5, 3.9, by = 0.01),
                    "logPhi" = seq(2, 2.6, by = 0.01),
                    "logSigma" = seq(-2, -0.5, by = 0.01)),
      param = c(logR = 3.8, logSigma = log(0.3), logPhi = log(10)),
      nsim = 500)

## Not run:
# Plotting a contour of the logLikelihood
slice(object = ricker_sl,
      ranges = list("logR" = seq(3.5, 3.9, by = 0.01),
                    "logPhi" = seq(2, 2.6, by = 0.01),
                    "logSigma" = seq(-2, -0.5, by = 0.04)),
      pairs = TRUE,
      param = c(logR = 3.8, logSigma = log(0.3), logPhi = log(10)),
      nsim = 500, multicore = TRUE)

## End(Not run)

```

slik

Evaluates the synthetic log-likelihood.

Description

Evaluates the synthetic log-likelihood.

Usage

```
slik(object, param, nsim, multicore = FALSE, ncores = detectCores() - 1,
     cluster = NULL, ...)
```

Arguments

object	An object of class <code>synlik</code> .
param	Vector of parameters at which the synthetic likelihood will be evaluated.
nsim	Number of simulation from the model.
multicore	(logical) if TRUE the <code>object@simulator</code> and <code>object@summaries</code> functions will be executed in parallel. That is the <code>nsim</code> simulations will be divided in multiple cores.
ncores	(integer) number of cores to use if <code>multicore == TRUE</code> .
cluster	an object of class <code>c("SOCKcluster", "cluster")</code> . This allows the user to pass her own cluster, which will be used if <code>multicore == TRUE</code> . The user has to remember to stop the cluster.

... additional arguments to be passed to `object@simulator` and `object@summaries`. In general I would avoid using it and including `object@extraArgs` everything they need.

Value

The estimated value of the synthetic log-likelihood at `param`.

Author(s)

Matteo Fasiolo <matteo.fasiolo@gmail.com>

References

Simon N Wood. Statistical inference for noisy nonlinear ecological dynamic systems. *Nature*, 466(7310):1102–1104, 2010.

Examples

```
data(ricker_sl)
set.seed(643)
slik(ricker_sl, param = c(3.8, -1.2, 2.3), nsim = 500)
```

smcmc

MCMC parameter estimation for objects of class synlik.

Description

MCMC parameter estimation for objects of class `synlik`.

Usage

```
smcmc(object, initPar, niter, nsim, propCov, burn = 0,
       priorFun = function(param, ...) 0, targetRate = NULL, recompute = FALSE,
       multicore = !is.null(cluster), cluster = NULL, ncores = detectCores() -
       1, control = list(), ...)
```

Arguments

<code>object</code>	An object of class <code>synlik</code> .
<code>initPar</code>	see smcmc-class .
<code>niter</code>	see smcmc-class .
<code>nsim</code>	see smcmc-class .
<code>propCov</code>	see smcmc-class .
<code>burn</code>	see smcmc-class .
<code>priorFun</code>	see smcmc-class .

targetRate	see smcmc-class .
recompute	see smcmc-class .
multicore	see smcmc-class .
cluster	an object of class <code>c("SOCKcluster", "cluster")</code> . This allows the user to pass her own cluster, which will be used if <code>multicore == TRUE</code> . The user has to remember to stop the cluster.
ncores	see smcmc-class .
control	see smcmc-class .
...	additional arguments to be passed to <code>slik</code> function, see slik .

Value

An object of class `smcmc`.

Author(s)

Matteo Fasiolo <matteo.fasiolo@gmail.com>, code for adaptive step from the `adaptMCMC` package.

References

Vihola, M. (2011) Robust adaptive Metropolis algorithm with coerced acceptance rate. *Statistics and Computing*.

smcmc-class	smcmc-class
-------------	-------------

Description

Object representing the results of MCMC estimation on an object of class `synlik`, from which it inherits.

Slots

initPar Vector of initial parameters where the MCMC chain will start (`numeric`).

niter Number of MCMC iterations (`integer`).

nsim Number of simulations from the simulator at each step of the MCMC algorithm (`integer`).

burn Number of initial MCMC iterations that are discarded (`integer`).

priorFun Function that takes a vector of parameters as input and the log-density of the prior as output. If the output is not finite the proposed point will be discarded. (`function`). The function needs to have signature `fun(x, ...)`, where `x` represents the input parameters (`function`).

propCov Matrix representing the covariance matrix to be used to perturb the parameters at each step of the MCMC chain (`matrix`).

- targetRate** Target rate for the adaptive MCMC sampler. Should be in (0, 1), default is NULL (no adaptation). The adaptation uses the approach of Vihola (2011). (numeric)
- recompute** If TRUE the synthetic likelihood will be evaluated at the current and proposed positions in the parameter space (thus doubling the computational effort). If FALSE the likelihood of the current position won't be re-estimated (logical).
- multicore** If TRUE the `object@simulator` and `object@summaries` functions will be executed in parallel. That is the `nsim` simulations will be divided in multiple cores (logical).
- ncores** Number of cores to use if `multicore == TRUE` (integer).
- accRate** Acceptance rate of the MCMC chain, between 0 and 1 (numeric).
- chains** Matrix of size `niter` by `length(initPar)` where the *i*-th row contains the position of the MCMC algorithm in the parameter space at the *i*-th (matrix).
- llkChain** Vector of `niter` elements where the *i*-th element is contains the estimate of the synthetic likelihood at the *i*-th iteration (numeric).
- control** Control parameters used by the MCMC sampler:
- `theta` = controls the speed of adaption. Should be between 0.5 and 1. A lower gamma leads to faster adaption.
 - `adaptStart` = iteration where the adaption starts. Default 0.
 - `adaptStop` = iteration where the adaption stops. Default `burn + niter`
 - `saveFile` = path to the file where the intermediate results will be stored (ex: "`~/Res.RData`").
 - `saveFreq` = frequency with which the intermediate results will be saved on `saveFile`. Default 100.
 - `verbose` = if TRUE intermediate posterior means will be printer.
 - `verbFreq` = frequency with which the intermediate posterior means will be printer. Default 500.

Author(s)

Matteo Fasiolo <matteo.fasiolo@gmail.com>

References

Vihola, M. (2011) Robust adaptive Metropolis algorithm with coerced acceptance rate. *Statistics and Computing*.

Examples

```
# Load "synlik" object
data(ricker_sl)

plot(ricker_sl)

# MCMC estimation
set.seed(4235)
ricker_sl <- smcmc(ricker_sl,
                  initPar = c(3.2, -1, 2.6),
                  niter = 50,
                  burn = 3,
```

```

      priorFun = function(input, ...) 1,
      propCov = diag( c(0.1, 0.1, 0.1) )^2,
      nsim = 200,
      multicore = FALSE)

# Continue with additional 50 iterations
ricker_sl <- continue(ricker_sl, niter = 50)

plot(ricker_sl)

```

 synlik-class

 synlik-class

Description

Basic class for simulation-based approximate inference using Synthetic Likelihood methods.

Usage

```
synlik(...)
```

Arguments

... See section "Slots".

Slots

param Named vector of parameters used by `object@simulator` (numeric).

simulator Function that simulates from the model (function). It has to have prototype `fun(param, nsim, extraArgs, ...)`. If `summaries()` is not specified the `simulator()` has output a matrix with `nsim` rows, where each row is a vector of simulated statistics. Otherwise it can output any kind of object, and this output will be passed to `summaries()`.

summaries Function that transforms simulated data into summary statistics (function). It has to have prototype `fun(x, extraArgs, ...)` and it has to output a matrix with `nsim` rows, where each row is a vector of simulated statistics. Parameter `x` contains the data.

data Object containing the observed data or statistics (ANY).

extraArgs List containing all the extra arguments to be passed to `object@simulator` and `object@summaries` (list).

plotFun Function that will be used to plot `object@data`. Prototype should be `fun(x, ...)` (function).

Author(s)

Matteo Fasiolo <matteo.fasiolo@gmail.com>

References

Simon N Wood. Statistical inference for noisy nonlinear ecological dynamic systems. *Nature*, 466(7310):1102–1104, 2010.

Examples

```
#### Create Object
ricker_sl <- synlik(simulator = rickerSimul,
                  summaries = rickerStats,
                  param = c( logR = 3.8, logSigma = log(0.3), logPhi = log(10) ),
                  extraArgs = list("nObs" = 50, "nBurn" = 50),
                  plotFun = function(input, ...)
                      plot(drop(input), type = 'l', ylab = "Pop", xlab = "Time", ...))
)

# Simulate from the object
ricker_sl@data <- simulate(ricker_sl)
ricker_sl@extraArgs$obsData <- ricker_sl@data # Needed by WOOD2010 statistics

plot(ricker_sl)
```

Index

ANYOrNULL-class, 4

bf, 5
bf1 (bf), 5
bf2 (bf), 5
bf3 (bf), 5
blow_sl, 7, 7
blow_smcmc (blow_sl), 7
blowC (internal_C), 12
blowSimul, 6, 7
blowStats (blow_sl), 7

checkBoundsCpp (internal_C), 12
checkNorm, 8
cleanStats (internal_C), 12
continue, 10
continue, smcml-method (continue), 10

extractCorr, 11

functionOrNULL-class, 11

internal_C, 12

nlar, 12
numericOrNULL-class, 13

order_reg (internal_C), 12
orderDist, 13

plot, 15, 16
plot, smcml, missing-method (plot-smcml), 14
plot, synlik, missing-method (plot-synlik), 15
plot-smcml, 14
plot-synlik, 15

ricker_sl, 17, 18
ricker_smcml (ricker_sl), 18
rickerSimul, 16, 18

rickerStats (ricker_sl), 18
robCov, 19

simpleModelsWrap (internal_C), 12
simulate, 20
simulate, synlik-method, 20
slAcf, 21
slacf (internal_C), 12
slice, 22
slik, 10, 22, 23, 25
slnlar (internal_C), 12
smcml, 24
smcml-class, 25
synlik (synlik-class), 27
synlik-class, 27
synlik-package, 2